TECHNICAL FEATURES

	Engine	Fuel	Starter	Power kW/hp	Transmission	Speeds FWD+REV	Quick reverser	Clutch	Brakes	Differential	РТО	Handlebar	Available wheels	Safety devices	Ferrari attachments which can be mounted
306 PowerSafe® SMART	GENKINS GK210	Gasoline	Recoil	4,4 / 5,9	Mechanical, with gears and worm screw in oil bath	1+1	No	PowerSafe®, hydraucally operated with multiple discs in oil bath	No	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent- blocks, adjustable in height, sideways and reversible	3.50-8 4.00-8 4.0-10 Steel cage wheels Ø43 cm	In compliance with the EN 709/A4 standard	Rotary hoe, cutter bar, lawn mower, snow blade, sweeper
328 PowerSafe®	HONDA GP160	Gasoline	Recoil	3,6 / 4,8	Mechanical, with gears and worm screw in oil bath	3+3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraucally operated with multiple discs in oil bath	Parking brake	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent- blocks, adjustable in height, sideways and reversible	4.00-8 4.0-10 5.0-10 5.0-12 6.5/80-12 Steel cage wheels Ø43 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, cutter bar, lawn mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	HONDA GX200	Gasoline	Recoil	4,1 / 5,5											
	HONDA GX270	Gasoline	Recoil	6,3 / 8,6											
338 PowerSafe®	HONDA GX270	Gasoline	Recoil or electric	6,3/8,6	- Mechanical, with gears and worm screw in oil bath	3+3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraucally operated with multiple discs in oil bath	Parking brake on the two wheels	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent- blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	HONDA GX340	Gasoline	Recoil	8 / 10,7											
	KOHLER KD350	Diesel	Recoil or electric	5,5 / 7,5											
340 PowerSafe®	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	Mechanical, with gears and worm screw in oil bath	3+3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraucally operated with multiple discs in oil bath	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent- blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 6.5/80-15 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil or electric	6,8 / 9,1											
	KOHLER KD440	Diesel (with air filter in oil bath)	Electric	8 / 10,5											
360 PowerSafe®	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	Mechanical, with gears and worm screw in oil bath	3+3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraucally operated with multiple discs in oil bath	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent- blocks, adjustable in height, sideways and reversible	6.5/80-12 6.5/80-15 Steel cage wheels Ø 58 cm	In compliance with the EN 709/A4 standard	Rotary hoe, ridger, plough, mulching machine, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, sweeper
	KOHLER KD440	Diesel (with air filter in oil bath)	Recoil or electric	8 / 10,5											
					1	l		ı			1	l	l	ı	Rotary hoe, PDR,
380HY STARGATE	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	Hydrostatic StarGate, with final worm screw	One-speed range in both FWD and REV	Yes, by hydrostatic unit with EasyGrip lever on the handlebar	PowerSafe®, hydraucally operated with multiple discs in oil bath	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent- blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 6.5/80-15 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil or electric	6,8 / 9,1	reduction in oil bath										

For more info, size and weights go to $\underline{\text{www.ferrariagri.com}}$

42 43