TECHNICAL FEATURES

	Engine	Fuel	Starter	Power kW/HP	Gearbox	Speeds FWD + REV	Quick reverser	Clutch	Brakes	Differential	PT0	Handlebar	Wheels	Safety devices	FERRARI attachments which can be mounted
320 TRENDY	HONDA GX200	Gasoline	Recoil	4.1 / 5.5	With gears and worm screw in oil bath	3 + 2 (two-wheel tractor position) 2 + 2 (motor mower position)	Yes	Self-ventilating dry clutch, with manual control	No	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	4.00-8 4.0-10 6.5/80-12 Steel cage wheels Ø 43 cm	Engine Stop combined with clutch and contrast reverse speed	Rotary hoe, PDR, ridger, plough, cutter bar, lawn mower, BladeRunner, snow blade and turbine snow thrower, sweeper, towed trailer
	HONDA GX270	Gasoline	Recoil	6.3 / 8.6											
	KOHLER KD350	Diesel	Recoil	5.5 / 7.5											
					I	l			I			I	I	I	
330 TRENDY	HONDA GX270	Gasoline	Recoil	6.3 / 8.6	- With gears and worm screw in oil bath	3 + 2 (two-wheel tractor position) 2 + 2 (motor mower position)	Yes	Self-ventilating dry clutch, with manual control	No	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	Engine Stop combined with clutch and contrast reverse speed	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper, towed trailer
	HONDA GX340	Gasoline	Recoil	8 / 10.7											
	KOHLER KD350	Diesel	Recoil or electric	5.5 / 7.5											
		I	I	I	ı	I	I	I	I	I	I	I	I	I	l
340 TRENDY	HONDA GX390	Gasoline	Recoil or electric	8.7 / 11.7	With gears and worm screw in oil bath	4 + 3 (two-wheel tractor position) 3 + 3 (motor mower position)	Yes	Self-ventilating dry clutch, with manual control	Independent working brakes on the two wheels	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	Engine Stop combined with clutch and contrast reverse speed	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper, towed trailer, work and travel sulky
	YANMAR L100V	Diesel	Recoil or electric	6.8 / 9.1											
	KOHLER KD440	Diesel	Recoil or electric	8 / 10.5											

For more info, size and weights go to www.ferrariagri.com

26 27