

TECHNICAL FEATURES

	Engine	Fuel	Starter	Power kW/hp	Transmission	Speeds FWD+REV	Quick reverser	Clutch	Differential	PTO	Brakes	Reduction units	Handlebar	Safety devices	FERRARI attachments which can be mounted
514 PowerSafe®	HONDA GP160	Gasoline	Recoil	3,6 / 4,8	Mechanical, with gears and worm screw in oil bath	1 + 1	Yes, with mechanical control	PowerSafe®, hydraulic with manual control	No	Independent from gearbox. At 990 rpm with engagement in oil bath	No	No	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, snow blade
515 PowerSafe®	HONDA GP160	Gasoline	Recoil	3,6 / 4,8	Mechanical, with gears and worm screw in oil bath	3 + 3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraulic with manual control	No	Independent from gearbox. At 990 rpm with engagement in oil bath	No	No	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, snow blade
	HONDA GX200	Gasoline	Recoil	4,1 / 5,5											
	HONDA GX270	Gasoline	Recoil	6,3 / 8,6											
518 PowerSafe®	HONDA GP160	Gasoline	Recoil	3,6 / 4,8	Mechanical, with gears and worm screw in oil bath	3 + 3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraulic with manual control	With lock	Independent from gearbox. At 990 rpm with engagement in oil bath	No	No	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, snow blade
	HONDA GX270	Gasoline	Recoil	6,3 / 8,6											
530 PowerSafe®	HONDA GX270	Gasoline	Recoil	6,3 / 8,6	Mechanical, with gears and worm screw in oil bath	3 + 3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraulic with manual control	With lock	Independent from gearbox. At 990 rpm with engagement in oil bath	Independent working brakes on the two wheels and parking brake	No	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	KOHLER KD350	Diesel	Recoil	5,5 / 7,5											
530^S PowerSafe®	HONDA GX340 ALPS	Gasoline	Recoil	8 / 10,7	Mechanical, with gears and worm screw in oil bath. Cast-iron reinforced gearbox	3 + 3	Yes, with mechanical control on the handlebar	PowerSafe®, hydraulic with manual control	Steering clutches combined with brakes	Independent from gearbox. At 990 rpm with engagement in oil bath	Steering clutch/brake assembly on the two wheels and parking brake	Cascade of gears in oil bath on the two wheels	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil	6,8 / 9,1											
530^S EasyDrive® PowerSafe®	HONDA GX340 ALPS	Gasoline	Recoil	8 / 10,7	Mechanical, with gears and worm screw in oil bath. Cast-iron reinforced gearbox	3 + 3	Yes, with EasyDrive® hydromechanical control on the handlebar	PowerSafe®, hydraulic with manual control	Steering clutches combined with brakes	Independent from gearbox. At 990 rpm with engagement in oil bath	Steering clutch/brake assembly on the two wheels and automatic parking brake	Cascade of gears in oil bath on the two wheels	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil	6,8 / 9,1											
535^{HY} PowerSafe®	HONDA GX340 ALPS	Gasoline	Recoil	8 / 10,7	Hydrostatic, with final worm screw reduction in oil bath	2-speed ranges (slow/fast) in both FWD and REV	Yes, by hydrostatic unit with EasyRider rotating knob on the handlebar	PowerSafe®, hydraulic with manual control	With lock	Independent from gearbox. At 990 rpm with engagement in oil bath	Independent working brakes on the two wheels and parking brake	No	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil	6,8 / 9,1											
560^{HY WS} PowerSafe®	HONDA GX390 ALPS	Gasoline	Recoil	8,7 / 11,7	Hydrostatic, with final worm screw reduction in oil bath	2-speed ranges (slow/fast) in both FWD and REV	Yes, by hydrostatic unit with EasyRider rotating knob on the handlebar	PowerSafe®, hydraulic with manual control	Hydraulically controlled steering clutches in oil bath combined with brakes	Independent from gearbox. At 990 rpm with engagement in oil bath	Steering clutch/brake assembly on the two wheels and automatic parking brake	Cascade of gears in oil bath on the two wheels	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade, sweeper
	BRIGGS&STRATTON 16 HP VANGUARD	Gasoline	Recoil	11,9 / 16											
	YANMAR L100V	Diesel	Recoil	6,8 / 9,1											
580^{HY} STARGate	HONDA GX270 ALPS	Gasoline	Recoil	6,3 / 8,6	Hydrostatic StarGate, with final worm screw reduction in oil bath	One-speed range in both FWD and REV	Yes, by hydrostatic unit with EasyGrip lever on the handlebar	PowerSafe®, hydraulic with manual control	With lock	Independent from gearbox. At 990 rpm with engagement in oil bath	Independent working brakes on the two wheels and parking brake	No	Mounted on silent-blocks, adjustable in height and sideways	In compliance with the EN 12733 standard	Cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	HONDA GX340 ALPS	Gasoline	Recoil	8 / 10,7											
	YANMAR L100V	Diesel	Recoil	6,8 / 9,1											